

# Package: dadjokeapi (via r-universe)

September 11, 2024

**Type** Package

**Title** Return a Random Dad Joke

**Version** 1.0.2

**URL** <https://github.com/jhollister/dadjokeapi/>

**BugReports** <https://github.com/jhollister/dadjokeapi/issues/>

**Maintainer** Jeffrey Hollister <hollister.jeff@epa.gov>

**Description** What is funnier than a dad joke? A dad joke in R! This package utilizes the API for <<https://icanhazdadjoke.com>> and returns dad jokes from several API endpoints.

**License** MIT + file LICENSE

**Depends** R (>= 3.5.0)

**Imports** httr, beepr, curl, dplyr, png

**LazyData** true

**RoxygenNote** 7.1.1

**Suggests** testthat, mockery

**Repository** <https://jhollister.r-universe.dev>

**RemoteUrl** <https://github.com/jhollister/dadjokeapi>

**RemoteRef** HEAD

**RemoteSha** a6ccce0d6cd86e3300a40e2c4c7fc842df2f8872

## Contents

groan	2
groan_id	2
groan_image	3
groan_search	3

<b>Index</b>	<b>5</b>
--------------	----------

---

groan	<i>Function to return random dad joke</i>
-------	---

---

**Description**

This function returns a random dad joke(s) from <https://icanhazdadjoke.com>. as a message and invisibly as a character.

**Usage**

```
groan(sting = TRUE)
```

**Arguments**

sting	Plays a joke sting after the joke. Sound from <a href="https://archive.org/details/Rimshot_254">https://archive.org/details/Rimshot_254</a>
-------	---

**Value**

Invisibly returns a two item list with the first item holding the joke as a character and the second item containing the joke id as a character.

**Examples**

```
groan(sting = FALSE)
```

---

groan_id	<i>Function to return a specific dad joke</i>
----------	---

---

**Description**

This function returns a specific dad joke from <https://icanhazdadjoke.com> using its dad joke ID.

**Usage**

```
groan_id(joke_id)
```

**Arguments**

joke_id	A specific dad joke ID to return
---------	----------------------------------

**Value**

Returns a two item list with the first item holding the joke as a character and the second item containing the joke id as a character.

**Examples**

```
groan_id("G1GBIY0wAAAd")
```

---

groan_image	<i>Function to return a specific dad joke as an image</i>
-------------	---

---

**Description**

This function returns a specific dad joke as a png from <https://icanhazdadjoke.com> using its dad joke ID.

**Usage**

```
groan_image(joke_id)
```

**Arguments**

joke\_id            A specific dad joke ID to return

**Value**

Returns a png array from readPNG.

**Examples**

```
joke_png <- groan_image("G1GBIY0wAAAd")
```

---

groan_search	<i>Function to search and return dad jokes with specific terms</i>
--------------	--

---

**Description**

This function returns a specific dad joke as a png from <https://icanhazdadjoke.com> using its dad joke ID.

**Usage**

```
groan_search(term)
```

**Arguments**

term              A term to search <https://icanhazdadjoke.com>

**Value**

Returns a tibble of joke and joke id for jokes that contain the search term.

**Examples**

```
groan_search(term = "cat")
```

# Index

groan, [2](#)  
groan\_id, [2](#)  
groan\_image, [3](#)  
groan\_search, [3](#)